

DECLARATION OF PERFORMANCE

DECLARATION OF PERFORMANCE NO.

PTRL-DoP/MW/15/20

UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

PETRAROOF MW-EN13162-T5-CS(10)50-PL(5)550-WS-MU1

INTENDED USE OR USES

Factory made mineral wool (MW) products for thermal insulation of buildings.

PRODUCER

Head Office

Name: PETRALANA S.A.
Address: Konstytucji 74
41-905 Bytom, Poland

SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE

System 1 and System 3

HARMONIZED STANDARD

EN 13162:2012+A1:2015

NOTIFIED CERTIFICATION BODY OR BODIES


Wykonawca: Sieć Badawcza Łukasiewicz – Warszawski Instytut Technologiczny nr 1454
LUBUSKA UL. POLSKA 100

DECLARATION OF PERFORMANCE

DECLARED CHARACTERISTICS				
ESSENTIAL CHARACTERISTICS	REQUIREMENT CLAUSES IN THIS EUROPEAN STANDARD	SYMBOL	DECLARED LEVEL AND/OR CLASSES	UNIT
Reaction to fire	Reaction to fire	RtF	A1	Euroclass
Release of dangerous substances to the indoor environment	Release of dangerous substances	-	NPD	-
Acoustic absorption index for floors	Sound absorption	α_{PI} (API) i α_{WI} (AWI)	NPD	-
Impact noise transmission index (for floors)	Dynamic stiffness	s' SD	NPD	MN/m ³
	Thickness, dL	d _L	151-190	mm
	Compressibility, c	CP	NPD	mm
	Air flow resistivity	AFr	NPD	kPa·s/m ²
Direct airborne sound insulation index	Air flow resistivity	AFr	NPD	kPa·s/m ²
Continuous glowing combustion	Continuous glowing combustion	-	NPD	-
Thermal resistance	Thermal resistance and thermal conductivity	R	Table-Thermal Resistance	m ² K/W
		λ	0,037	W/(mK)
	Thickness	d _N	151-190	mm
		Class for thickness tolerances	T5	mm
Water permeability	Short time water absorption	WS	<1	kg/m ²
	Long time water absorption	WL(P)	NPD	kg/m ²
Water vapour permeability	Water vapour transmission	MU	MU1	-
Compressive strength	Compressive stress or compressive strength	CS(10)	50	kPa
	Point load	PL(5)	550	N
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics	Reaction to fire	A1	Euroclass
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and thermal conductivity	R	Table-Thermal Resistance	m ² K/W
		Declared λ	0,037	W/(mK)
	Dimensional stability under specified temperature	DS (70,90)	NPD	%
	Dimensional stability under specified temperature and humidity conditions		NPD	%
Tensile/Flexural strength	Tensile strength perpendicular to faces	TR	NPD	kPa
Durability of compressive strength against ageing/degradation	Compressive creep	CC(i1/i2/y)5c	NPD	mm

THERMAL RESISTANCE R _D																
d _N [mm]	151	160	170	180	190	-	-	-	-	-	-	-	-	-	-	-
R _D [m ² KW]	4,05	4,30	4,55	4,85	5,10	-	-	-	-	-	-	-	-	-	-	-

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued with respect to Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

QUALITY DEPARTMENT AND CERTIFICATION MANAGER	
Place: <u>Bytom</u>	Date: <u>08.05.2025</u>
KIEROWNIK DZIAŁU KONTROLI JAKOŚCI  mgr inż. Dawid Gutuch	