

**DECLARATION OF PERFORMANCE
PETRAROOF -T d = 20-29 mm**

DECLARATION OF PERFORMANCE NO.

PTRL-DoP/MW/15/28

UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

PETRAROOF-T MW-EN13162-T5-CS(10)80-PL(5)800-WS-MU1

INTENDED USE OR USES

Factory made mineral wool (MW) products for thermal insulation of buildings.

PRODUCER

Head Office	Factory
Name: PETRALANA S.A.	Name: PETRALANA S.A.
Address: Str. Mazowiecka 11	Address: Str. Konstytucji 74
40-732 Katowice, Poland	41-905 Bytom, Poland
Phone: +48 32 209 01 27	Phone: +48 32 770 05 00

SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE

System 1 and System 3

HARMONIZED STANDARD

EN 13162:2012+A1:2015 „Thermal insulation products for buildings – Factory made mineral wool (MW) products - Specification”

NOTIFIED CERTIFICATION BODY OR BODIES

Sieć Badawcza Łukasiewicz – Warszawski Instytut Technologiczny nr 1454

DECLARATION OF PERFORMANCE

DECLARED CHARACTERISTICS

ESSENTIAL CHARACTERISTICS	REQUIREMENT CLAUSES IN THIS EUROPEAN STANDARD	SYMBOL	DECLARED LEVEL AND/OR CLASSES	UNIT
Reaction to fire Euroclass characteristics	Reaction to fire	Rf	A1	Euroclass
Release of dangerous substances to the indoor	Release of dangerous substances	-	NPD	-
Acoustic absorption index	Sound absorption	α_{PI} (API) i α_{WI} (AWi)	NPD	-
Impact noise transmission index	Dynamic stiffness	s' SD	NPD	MN/m ²
	Thickness, dL	dL	20-29	mm
	Compressibility, c	CP	NPD	mm
	Air flow resistivity	AFr	NPD	kPa.s/m ²
Direct airborne sound insulation index	Air flow resistivity	AFr	NPD	kPa.s/m ²
Continuous glowing combustion	Continuous glowing combustion	-	NPD	-
Thermal resistance	Thermal resistance and thermal conductivity	R	Table-Thermal Resistance	m ² K/W
		λ	0,039	W/mK
Water permeability	Short time water absorption	WS	<1	kg/m ²
	Long time water absorption	WL(P)	NPD	kg/m ²
Water vapour permeability	Water vapour transmission	MU	MU1	-
Compressive strength	Compressive stress or compressive strength	CS(10/Y)	80	kPa
	Point load	PL	800	N
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics	Reaction to fire	A1	Euroclass
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and thermal conductivity	Declared λ	0,039	W/mK
	Dimensional stability under specified temperature	DS	NPD	%
	Dimensional stability under specified temperature and humidity conditions		NPD	%
Tensile/Flexural strength	Tensile strength perpendicular to faces	TR	NPD	kPa
Durability of compressive strength against ageing/degradation	Compressive creep	CC(1/12/y)6c	NPD	mm

THERMAL RESISTANCE R_D

d [mm]	20	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
R _D [m ² K/W]	0,50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued with respect to Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

QUALITY DEPARTMENT AND CERTIFICATION MANAGER

KIEROWNIK
DZIAŁU KONTROLI JAKOŚCI
mgr inż. Dawid Gofuch

Place: BytomDate: 13.04.2023

Signature