

TECHNICAL DATA SHEET

PETRAFAS-M



Slabs of stone wool for internal and external building objects for thermal, acoustic and fire insulation

OFFICIAL DOCUMENTATION:

Declaration of Performance:
Nr PTRL-DoP/MW/15/34
Nr PTRL-DoP/MW/15/10
Nr PTRL-DoP/MW/15/26
Nr PTRL-DoP/MW/22/123



APPLICATION:

- external and partition walls insulated by ETICS system
- external monolithic, prefabricated and brick walls
- jambs insulation
- fire insulation of attics (reaction to fire classification - A1)
- acoustic and fire insulation of staircases (reaction to fire classification - A1)

FACTORY:

PETRALANA S.A.
Konstytucji 74 Street
41-905 Bytom
Poland
+48 32 770 05 00
office@petralana.eu

PRODUCT CODE
PETRAFAS-M MW-EN13162-T5-DS(70,90)-CS(10)30-TR10-WS-WL(P)-MU1 (d=20-29mm) PETRAFAS-M MW-EN13162-T5-DS(70,90)-CS(10)30-TR10-WS-WL(P)-MU1,AW0,80 (d=30-49 mm) PETRAFAS M MW-EN13162-T5-DS(70,90)CS(10)30 TR15-WS WL(P)-MU1-AW0,80 (d=50-99 mm) PETRAFAS-M MW-EN13162-T5-DS(70,90)-CS(10)40-TR 15-WS-WL(P)-MU1-AW0,80 (d=100-190 mm)
DECLARED THERMAL CONDUCTIVITY COEFFICIENT λ_D
$\leq 0,035$ [W/(mK)]

DECLARED PARAMETERS			
DECLARED PROPERTIES OF THE PRODUCT ACC. TO EN 13162:2012+A1:2015	SYMBOL	CLASS OR TOLERANCE	UNITS
Class for thickness tolerances	T	T5	-1 mm / +3 mm
			-1 % / +3 mm
Dimensional stability under 70°C and 90% humidity	DS(70,90)	$\leq 1,0$	[-]
Compressive stress at 10% deformation	CS(10/Y)	30 (d=20-99 mm) 40 (d=100-190 mm)	[kPa]
Tensile strength perpendicular to faces	TR	$\geq 10,0$ (d=20-49 mm) $\geq 15,0$ (d=50-190 mm)	[kPa]
Point load at 5mm deformation	PL(5)	NPD	[N]
Short time water absorption	WS	$\leq 1,0$	[kg/m ²]
Long time water absorption	WL(P)	$\leq 3,0$	[kg/m ²]
Water vapour transmission	MU	MU1	[-]
Sound Absorption Index	AW	0,80(d=30-190mm)	[-]
Reaction to fire	RtF	A1	Euroclass

DECLARED THERMAL RESISTANCE R_D													
d [mm]	20	30	40	50	100	120	150	-	-	-	-	-	-
R_D [m ² K/W]	0,55	0,85	1,10	1,40	2,85	3,40	4,25	-	-	-	-	-	-

DIMENSIONS AND PACKING									
FORMAT OF PLATES			PACKAGES			PALLETS			
Length	Width	Thickness	No. of plates in a package	Cover surface of a package	Volume of a package	No. of plates on a pallet	Cover surface of plates on a pallet	Volume of plates on a pallet	
[mm]	[mm]	[mm]	[pcs.]	[m ²]	[m ³]	[pcs.]	[m ²]	[m ³]	
1000	600	20	15	9,00	0,180	16	144,00	2,880	
		30	10	6,00	0,180	16	96,00	2,880	
		40	6	3,60	0,144	20	72,00	2,880	
		50	6	3,60	0,180	16	57,60	2,880	
		100	3	1,80	0,180	16	28,80	2,880	
		120	2	1,20	0,144	20	24,00	2,880	
		150	2	1,20	0,180	16	19,20	2,880	
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-